

# इंटरनेट

# मानक

## Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 8271-3-1 (1982): Specification, for Quartz Crystal Units Used for Frequency Control and Selection, Part 3: Series bc for Oscillators, Section 1: Quartz Crystal Unit Type BC-01 [LITD 5: Semiconductor and Other Electronic Components and Devices]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



Indian Standard



SPECIFICATION FOR  
QUARTZ CRYSTAL UNITS USED FOR FREQUENCY  
CONTROL AND SELECTION

PART III SERIES BC FOR OSCILLATORS

Section 1 Quartz Crystal Unit Type BC-01

- 0. General** — This standard shall be read in conjunction with IS : 8271 ( Part I )-1981 ' Specification for quartz crystal units used for frequency control and selection; Part I General requirements and tests ( first revision ) '.
- 1. Outline and Dimensions** — Holder outline shall conform to Type BC ( see Sheet No. 5 of IS : 4570-1968 Specification for crystal holders ).
- 2. Marking** — See 8 of IS : 8271 ( Part I )-1981.
- 3. Construction and Workmanship** — See 7 of IS : 8271 ( Part I )-1981.
- 4. Test Schedule and Detail Requirements**
- 4.1 General Conditions for Test** — See 9.2 of IS : 8271 ( Part I )-1981.
- 4.2 Test Schedule** — The sequence and grouping of type, routine and acceptance tests shall be as per 9.1 of IS : 8271 ( Part I )-1981.
- 4.3 Detail Requirements** — The detail requirements applicable to this particular type of crystal unit shall be as specified in Table 1.

TABLE 1 DETAIL REQUIREMENTS OF QUARTZ CRYSTAL UNIT TYPE BC-01

SI No.	Characteristic	Requirement
(1)	(2)	(3)
i)	Type of holder	BC ( See 1 )
ii)	Frequency range	5 to 20 MHz
iii)	Frequency tolerance:	
	a) Over operating temperature: range	± 50 ppm
iv)	Resonance resistance	See Table 2
v)	Mode of oscillation	Fundamental
vi)	Load capacitance	Infinity (series)
vii)	Capacitance shunt	7 pF Max
viii)	Operating temperature range	-55°C to +105°C
ix)	Test set, calibration values and rated drive level	See Table 3
x)	Shock [ as per 9.15 ( Severity A ) of IS : 8271 ( Part I ) - 1981 ]:	
	a) Frequency change permitted	± 5 ppm
	b) Resonance resistance change permitted	± 10 percent

( Continued )

TABLE 1 DETAIL REQUIREMENTS OF QUARTZ CRYSTAL UNIT TYPE BC-01 — Contd

SI No.	Characteristic	Requirement
(1)	(2)	(3)
xi)	Vibration [ as per 9.16.1 ( Severity A ) of IS : 8271 ( Part I )-1981 ]:	
	a) Frequency change permitted	± 5 ppm
	b) Resonance resistance change permitted	± 10 percent
xii)	Temperature cycling:	
	a) Frequency change permitted	± 5 ppm
	b) Resonance resistance change permitted	± 10 percent
xiii)	Temperature run:	
	a) Frequency change permitted	± 5 ppm
	b) Resonance resistance change permitted	± 10 percent
xiv)	Ageing	5 ppm
	Frequency change permitted	

TABLE 2 RESONANCE RESISTANCE

[ Table 1, Item (iv) ]

Frequency Range MHz	Maximum Resonance Resistance Ohms
(1)	(2)
From 5 to 7	50
Over 7 to 10	30
Over 10 to 15	25
Over 15 to 20	20

TABLE 3 TEST SET, CALIBRATION VALUES AND RATED DRIVE LEVEL

[ Table 1, Item (ix) ]

SI No.	Frequency Range MHz	Calibration Values			Rated Drive Level mW
		Resistance Ohms	Crystal Current mA	Resistor Voltage Drop V	
(1)	(2)	(3)	(4)	(5)	(6)
i)	From 5 to 7.5	25	14	—	5.0 ± 1.0
ii)	Over 7.5 to 10	16	18	—	
iii)	Over 10 to 15	13	20	—	
iv)	Over 15 to 20	12	—	0.24	

For SI No. (i) to (iii) — Test Set TS-330/TSM.

For SI No. (iv) — Test Set TS-683/TSM.